DHI-NVR2108-8P-4KS3-V2

Dahua 8CH 1-Bay Smart 1U NETWORK VIDEO RECORDER



- Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.
- Max decoding capability: 6 × 1080p@30 fps.
- Max 144/144/72 Mbps incoming/recording/outgoing bandwidth.
- Supports IP cameras with a resolution up to 12 MP.
- AI by Recorder supports 4-channel SMD Plus.
- AI by Camera supports perimeter protection and SMD.
- Supports one-click arming and disarming.



Series Overview

The NVR2000-4KS3-V2 model of the Lite Series NVR is favored for its outstanding performance. It supports 4K resolution for scenes that require highly detailed images, and can serve as the edge, central, or backup storage with an intuitive shortcut menu for remote management and control. This NVR also features Smart Motion Detection (SMD) by recorder, which can distinguish target vehicles and humans from ordinary ones in real-time. This NVR is both cost-effective and easy-to-install, making it ideal for a wide range of applications such as villas, shops and other small and medium-sized scenes.

Functions

SMD Plus

With intelligent algorithm, Dahua Smart Motion Detection technology can categorize the targets that trigger motion detection and filter the motion detection alarm triggered by non-concerned targets to realize effective and accurate alarm.

Perimeter Protection by Camera

Automatically filters out false alarms caused by animals, rustling leaves, bright lights, etc. Enables system to act secondary recognition for the targets. Improves alarm accuracy.

HDMI (4K)

The HDMI port can support up to 4K output, delivering clear and highly detailed images.

NVR NEXT

With its enhanced system, the NVR introduces NVR NEXT, a user-friendly GUI featuring a modular design to improve operation efficiency and streamline workflows, catering to the needs of small and medium-sized businesses.

Technical Specification

System

Main Processor	Industrial-grade processor
Operating System	Embedded Linux
Operating Interface	Web; Local GUI

AI

AI by Recorder	SMD Plus
AI by Camera	Perimeter protection; SMD

Perimeter Protection

Perimeter Performance of AI by Camera (Number of Channels)	All channels (4 targets/s)

SMD

SMD Plus by Recorder	4 channels: Secondary filtering for human and motor vehicle, reducing false alarms caused by leaves, rain and lighting condition change
SMD by Camera	All channels (8 targets/s)

Audio and Video

Access Channel	8 channels
Network Bandwidth	AI disabled: 144 Mbps incoming, 144 Mbps recording and 72 Mbps outgoing; AI enabled: 72 Mbps incoming, 72 Mbps recording and 36 Mbps outgoing
Resolution	12 MP;8 MP;6 MP;5 MP;4 MP;3 MP;1080p;720p;960p;D1;CIF;QCIF
Decoding Capability	AI disabled: 1-channel 12 MP@30 fps; 1-channel 8 MP@30 fps; 2-channel 6 MP@30 fps; 2-channel 5 MP@30 fps; 3-channel 4 MP@30 fps; 6-channel 1080p@30 fps; AI enabled: 1-channel 8 MP@30 fps; 2-channel 6 MP@30 fps; 2-channel 5 MP@30 fps; 3-channel 4 MP@30 fps; 6-channel 1080p@30 fps
Video Output	1 HDMI, 1 VGA HDMI: 3840 × 2160, 1920 × 1080, 1280 × 1024, 1280 × 720 VGA: 1920 × 1080, 1280 × 1024, 1280 × 720
Multi-screen Display	1/4/8/9
Third-party Camera Access	ONVIF

Compression Standard

Video Compression	Smart H.265+;H.265;Smart H.264+;H.264;MJPEG
Audio Compression	G.711a;G.711u;PCM;G726

Network

Network Protocol	HTTP; HTTPS; TCP/IP; IPv4; IPv6; RTSP; UDP; NTP; DHCP; DNS; SMTP; IP Filter; DDNS; IP Search (Supports IP camera, DVR, NVS, etc.); P2P; Auto Registration
Mobile Phone Access	iOS;Android
Interoperability	ONVIF 26.06 (Profile T; Profile S; Profile G); CGI; SDK
Browser	Chrome;firefox;IE;Safari;Edge
Security	Digest;WSSE;Account lockout;Security logs;IP/MAC filtering;Generation and importing of X.509 certification;syslog;HTTPS;802.1x;Trusted boot;Trusted execution;Trusted upgrade;Session security;Security warning;SSL/TLS1.2;AES 256

Recording Playback

Multi-channel Playback	Up to 8 channels
Record Mode	General, motion detection; intelligent; alarm
Backup Method	USB device and network
Playback Mode	Instant playback; general playback; event playback; tag playback; smart playback

Alarm

General Alarm	Motion detection; camera external alarm; PIR alarm
Anomaly Alarm	Error (no disk, disk error, low space, low quota space; network disconnection; IP conflict; MAC conflict); video loss; video tampering; camera offline
Intelligent Alarm	perimeter protection (intrusion and tripwire); SMD Plus
Alarm Linkage	Recording; snapshot; buzzer; log; preset; email; tour

Port

Audio Input	1-channel RCA
Audio Output	1-channel RCA
Disk Interface	1 SATA port, up to 20 TB. This limit varies depending on the environment temperature.
USB	2 (2 rear USB 2.0 ports)
HDMI	1
VGA	1
Network Port	1 (10/100/1000 Mbps Ethernet port, RJ-45)
PoE Port	8 ports, 10/100 Mbps, IEEE 802.3 af/at


General

Power Supply	53 VDC, 1.81A
Power Consumption	<10 W (without HDD) Total output power of PoE is 78 W, the maximum output power of a single port is 25.5 W
Net Weight	0.69 kg (1.52 lb)
Gross Weight	1.71 kg (3.77 lb)
Product Dimensions	270.0 mm × 206.4 mm × 45.9 mm (10.63" × 8.13" × 1.81") (W × D × H)
Packaging Dimensions	427.0 mm × 96.0 mm × 262.0 mm (16.81" × 3.78" × 10.31") (W × D × H)
Operating Temperature	–10 °C to +55 °C (+14 °F to +131 °F)
Storage Temperature	–20 °C to +60 °C (–4 °F to +140 °F)
Operating Humidity	10%–93% (RH), non-condensing
Certifications	CE-LVD: EN IEC62368-1:2024+A11:2024; CE-EMC: EN55032:2015+A1:2020, EN55035:2017+A11:2020, EN IEC61000-3-2:2019+A1:2021, EN61000-3-3:2013+A2:2021


Ordering Information

Type	Model	Description
NETWORK VIDEO RECORDER	DHI-NVR2108-8P-4KS3-V2	Dahua 8CH 1-Bay Smart 1U NETWORK VIDEO RECORDER

Dimensions (mm[inch])



Panels



1 Ground
2 PoE Ports
3 VGA Port
4 AUDIO OUT, RCA Connector
5 HDMI Port
6 USB Ports
7 AUDIO IN, RCA Connector
8 Network Port
9 Power Input

Rev 002.000 ©2026 Dahua. All rights reserved. Design and specifications are subject to change without notice. Pictures in the document are for reference only, and the actual product shall prevail.