DS-7616NI-M2
16-ch 1U 8K NVR

- H.265+/H.265/H.264+/H.264 video formats
- Up to 16-ch IP camera inputs
- Up to 40 × 1080p@30 fps decoding capacity
- Up to 256 Mbps incoming bandwidth
- Up to 8-ch IP speakers can be connected

*Professional and Reliability
* H.265+ compression effectively reduces the storage space by up to 75%
* Dual-stream recording saves bandwidth
* Adopt stream over TLS encryption technology which provides more secure stream transmission service
* Support double verification for playback and downloading
*HD Video Output
* Provide independent HDMI and VGA outputs
* HDMI video output at up to 8K resolution
*Storage and Playback
* Up to 2 SATA interfaces for HDD connection
* 16-ch synchronous playback
*Smart & POS Function
* Support multiple VCA (Video Content Analytics) events
* Configurable special camera smart functions, such as VCA detection (motion, line crossing, intrusion, etc.), heat map, ANPR, and people counting
* POS information overlay on live view and playback, and POS triggered recording and alarm
*Network & Ethernet Access
* 2 self-adaptive 10/100/1000 Mbps Ethernet interfaces
* Hik-Connect for easy network management
* Smooth streaming technology
* Support web access without plug-in

▪ Specification

Video and Audio	
IP Video Input	16-ch Up to 32 MP resolution *: The NVR supports up to 8-ch 32/24/16 MP IP video inputs.
Incoming Bandwidth	256 Mbps
Outgoing Bandwidth	256 Mbps
HDMI Output	8K (7680 × 4320)/30Hz, 4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz
VGA Output	1920 × 1080/60Hz
Video Output Mode	HDMI/VGA independent output
CVBS Output	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480
Audio Output	1-ch, RCA (Linear, 1 KΩ)
Two-Way Audio	1-ch, RCA (2.0 Vp-p, 1 KΩ, using the audio input)
Decoding	
Decoding Format	H.265+/H.265/H.264+/H.264
Recording Resolution	32 MP/24 MP/16MP/12 MP/8 MP/7 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF *: The NVR supports up to 8-ch 32/24/16 MP IP video inputs, all channels for less than 16 MP.
Synchronous Playback	16-ch
Decoding Capability	2-ch@32 MP (30 fps); 3-ch@24 MP (30 fps); 4-ch@16MP (30 fps); 6-ch@12MP (30 fps);10-ch@8 MP (30 fps); 13-ch@6 MP (30 fps);16-ch@5 MP (30 fps);
Dual-Stream Recording	Support
Stream Type	Video, Video & Audio
Audio Compression	G.711ulaw/G.711alaw/G.722/G.726/AAC/MP2L2
Network	
Remote Connection	128
Network Protocol	TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS, ONVIF(Version 2.2), OTAP
Network Interface	2, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
Camera Access Protocol	ONVIF(Version 2.5), RTSP
Auxiliary Interface	
SATA	2 SATA interfaces
Capacity	Up to 16 TB capacity for each disk
Alarm In/Out	4/1
USB Interface	Front panel: 1 × USB 2.0; Rear panel: 1 × USB 3.0
General	
Power Supply	12 VDC, 3.33 A
Consumption	≤ 15 W (without HDD)
Working Temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working Humidity	10% to 90%
Dimension (W × D × H)	385 × 315× 52 mm (15.2" × 12.4" × 2.0")
Weight	≤ 3 kg (without HDD, 2.2 lb.)
Certification	
FCC	Part 15 Subpart B, ANSI C63.4-2014

CE	EN 55032:2015+A1:2020, ENIEC61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019, EN 50130-4:2011+A1:2014, EN 55035:2017+A11:2020
Cyber Security	
EN 303645	Support
Secure Boot	Support
Secure Component Verification SVC	Support
Password Protection	Support
IP & MAC Address Filtering	Support
HTTPS Encryption	Support
Live View & Playback Stream Encryption	Support
IEEE802.1X(EAP-TLS) Network Access Control	Support
Signed Firmware	Support
Ohters	Digest authentication User access log Centralized certificate management Brute force delay protection

▪ Physical Interface

No.	Description	No.	Description
1	LAN 1 and LAN 2 interfaces	6	USB 3.0 interface
2	Audio in and audio out	7	CVBS video output
3	HDMI interface	8	Power supply
4	Alarm in and alarm out	9	GND
5	VGA output	10	Power switch



▪ Dimension



Unit:mm [inch]

SCALE	1:1

See Far, Go Further

www.hikvision.com
support@hikvision.com

© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.

HIKVISION®