



S Series

MD8564-EH-V2 (6 mm)

5MP Mobile Dome Network
Camera



Technical Specifications

System Information

CPU	Multimedia SoC (System-on-Chip)
Flash	8 GB
RAM	2 GB

Camera Specifications

Image Sensor	1/2.7" Progressive CMOS
Max. Resolution	2560x1920 (5MP)
Lens Type	Fixed-focal
Focal Length	f = 6 mm
Aperture	F2.0
Iris Type	Fixed Iris
Field of View	50.0° (Horizontal) 37.0° (Vertical) 63.0° (Diagonal)
Shutter Time	1/5 sec. to 1/32,000 sec.
WDR Technology	WDR Pro
Day/Night	Yes
Removable IR-cut filter	Yes
Illuminators	Built-in IR illuminators, effective up to 50 meters with Smart IR, IR LED*4
Minimum Illumination	0.1 lux @ F2.0 (Color) 0.01 lux @ F2.0 (B/W) 0 lux with IR illumination on
Pan Range	max: ±0° ~ 25°

Tilt Range	max: 0° ~ +40°
Rotation Range	±170° (Tool-free)
Pan/Tilt/Zoom Functionalities	ePTZ: 48x digital zoom (4x on IE/Edge/Chrome plug-in, 12x built in)
Storage	Seamless Recording to MicroSD/SDHC/SDXC card

Video	
Compression	H.265, H.264, MJPEG
Maximum Frame Rate	30 fps @ 2560x1920 60 fps @ 1920x1080
Maximum Streams	3 simultaneous streams (Up to 8 configurable profiles)
S/N Ratio	65 dB
Dynamic Range	120 dB
Video Streaming	Adjustable resolution, quality and bitrate, Smart Stream III
Image Settings	<p>video title and time stamp overlay video orientation (flip, mirror, rotation), day/night settings illuminators, anti-overexposure Image settings size, quality and bit rate, white balance, image adjustment (brightness, contrast, saturation, sharpness, gamma curve), defog, 3DNR, HLM, EIS, scene mode (SignalLight, RailTrack)</p> <p>Exposure BLC, HLC, exposure control (exposure level, iris adjustment, exposure time, gain control, iris mode), AE speed adjustment, WDR</p> <p>Privacy mask Scheduled profile settings</p>

Network	
Users	Live viewing for up to 10 clients
Security	Access list, Account block, Audit log, Session timeout, Configurable password strength protection, Digest authentication, CSRF protection, HTTPS, IEEE 802.1x, Secure boot, Signed firmware, Trend Micro IoT Security (brute force attack event, cyberattack event), User access log, User account management
Protocols	802.1X, ARP, Bonjour, CIFS/SMB, CoS, DDNS, DHCP, DNS, FTP, HTTP, HTTPS, ICMP, IGMPv3, IPv4, IPv6, NTP, PPPoE, QoS, RTSP/RTP/RTCP, SFTP, SMTP, SNMP, SSL, TCP/IP, TLS, UDP, UPnP
Interface	10BASE-T/100BASE-TX Ethernet (M12, Female, 4-pin D-coded)
ONVIF	Profile G, S, T, M supported

AI Analytics	
Compute Capability	SoC with built-in hardware deep learning accelerator

Solution Integration	
VADP Package	Trend Micro (3-year free trial), Onboard AI(Smart Motion Detection)

Alarm and Event	
Event Trigger	Motion detection, Camera tampering detection, Manual trigger, Periodical trigger, System boot, Recording notification, SD card life expectancy, Shock detection, Cybersecurity events (brute force attack event, cyberattack event) with activated Trend Micro package.
Event Action	Event notification via email, HTTP, FTP/SFTP, NAS server, SD card, camera link, push notification File upload via email, HTTP, FTP/SFTP, NAS server, SD card

General	
Connectors	Single HL3 cable with distributed connectors: -M12 4-pin D-coded, Female connector for Network/PoE *1 -M12 5-pin A-coded, Male connector for DC 24V heater *1 Earth/grounding point M6 *1 Earth/grounding point M8 *1 Venting valve with water-proof breathable membrane *1
LED Indicator	System power and status indicator
Power Input	Camera: IEEE 802.3af PoE, B type, Class 0(37V~57V) Heater: DC 24V* *Comply with EN50155 #5.2 Table 4: Supply voltage limits and performance criteria
Power Consumption	Camera + IR: Max. 12.54W/7.24W (IR on/off) Heater: 48W (24V, 2A)
Dimensions	241 (D) x 162 (W) x 83 (H) mm
Weight	approx. 1490 g
Certifications	EMC CE (EN 55035, EN 55032 Class A), FCC (FCC Part 15 Subpart B Class A), RCM (AS/NZS CISPR 32 Class A), VCCI (VCCI-CISPR 32 Class A) Safety UL (UL 62368-1), CB (IEC/EN 62368-1, IEC/EN 60950-22, IEC/EN 62471) Environment IK10+, Casing with color RAL9011, IP68/6K9K, NEMA 4X, 5mm Heat-Strengthened glass with Anti-Reflection coating Railway EN 50155 2021 (OT4/ST1, nominal 24V DC), EN 50121-3-2:2016, EN 50121-4, EN 60068-2-1:2007, EN 60068-2-2:2007, EN 61373:2010, EN 45545-2, IEC 60571 Ed 3.0, IEC 62236-3-2 Ed 3.0 Automotive/Vehicles ECE R118 BI BSMI
Operating Temperature	Starting Temperature: -40°C ~ 70°C (-40°F ~ 158°F) Working Temperature: -40°C ~ 70°C (-40°F ~ 158°F) (IR off) -40°C ~ 65°C (-40°F ~ 149°F) (IR on)
Humidity	98% RH (non-condensing)
Storage Temperature	-40°C ~ 70°C (14°F ~ 158°F)
Warranty	60 months

System Requirements	
Operating System	Microsoft Windows 11/10/7 Mac 10.4 (Chrome only)
Web Browser	Chrome 110.0 or above Internet Explorer 10/11; Microsoft Edge
Other Players	VLC: 3.0 or above

Included Accessories	
Packing Contents	Quick installation guide, alignment sticker, screw driver, screw pack