



S Series

MD9560-DH (2.8 mm)

2MP Mobile Dome Network
Camera



Technical Specifications

System Information

CPU	Multimedia SoC (System-on-Chip)
Flash	128 MB
RAM	256 MB

Camera Specifications

Image Sensor	1/2.9" Progressive CMOS
Max. Resolution	1920x1080
Lens Type	Fixed-focal
Focal Length	f = 2.8 mm
Aperture	F1.8
Iris Type	Fixed Iris
Field of View	108.0° (Horizontal) 60.0° (Vertical) 124.0° (Diagonal)
Shutter Time	1/5 sec. to 1/32,000 sec.
WDR Technology	WDR Pro
Day/Night	Yes
Removable IR-cut filter	Yes
Illuminators	Built-in IR illuminators, effective up to 20 meters with Smart IR, IR LED*2
Minimum Illumination	0.13 lux @ F1.8 (Color) 0.01 lux @ F1.8 (B/W) 0 lux with IR illumination on
Pan Range	±30°

Tilt Range	90°
Rotation Range	±180°
Pan/Tilt/Zoom Functionalities	48x digital zoom (4x on IE plug-in, 12x built in)
Storage	Seamless Recording to MicroSD/SDHC/SDXC card

Video	
Compression	H.265, H.264, MJPEG
Maximum Frame Rate	30 fps @ 1920x1080
Maximum Streams	3 simultaneous streams
S/N Ratio	60 dB
Dynamic Range	120 dB
Video Streaming	Adjustable resolution, quality and bitrate, Smart Stream III
Image Settings	Adjustable image size, quality and bit rate; Time stamp, text overlay, flip & mirror; Configurable brightness, contrast, saturation, sharpness, white balance, exposure control, gain, backlight compensation, privacy masks; Scheduled profile settings, 3DNR, video rotation, defog

Audio	
Audio Capability	One-way Audio
Compression	G.711, G.726, MPEG-2 AAC-LC
Interface	Built-in microphone External microphone input
Effective Range	5 meters

Network	
Users	Live viewing for up to 10 clients
Security	Access list, Password protection, Digest authentication, HTTPS, IEEE 802.1x, Trend Micro IoT Security (brute force attack event, cyberattack event), User access log, User account management
Protocols	802.1X, ARP, CIFS/SMB, CoS, DDNS, DHCP, DNS, FTP, HTTP, HTTPS, ICMP, IGMP, IPv4, IPv6, NTP, PPPoE, QoS, RTSP/RTP/RTCP, SMTP, SNMP, SSL, TCP/IP, TLS, UDP, UPnP
Interface	10BASE-T/100BASE-TX Ethernet (M12, Female, 4-pin D-coded)
ONVIF	Profile G, S supported, specification available at www.onvif.org

Solution Integration	
VADP Package	Trend Micro (3-year free trial)
Video Motion Detection	Five-window video motion detection

Alarm and Event	
Event Trigger	Motion detection, Camera tampering detection, Audio detection, Digital input, Manual trigger, Periodical trigger, System boot, Recording notification, SD card life expectancy, Cybersecurity events (brute force attack event, cyberattack event)
Event Action	Event notification via email, HTTP, FTP, NAS server, SD card, digital output File upload via email, HTTP, FTP, NAS server, SD card

General	
---------	--

Connectors	M12 for Network connection *1 DC power input *1 Audio input *1 Digital input *1 (30V) Digital output *1 (12V, 50mA)
LED Indicator	System power and status indicator
Power Input	DC 7.5~48V
Power Consumption	Max. 5.5W (IR on) Max. 3.3W (IR off)
Dimensions	98 (D) x 54 (W) x 110 (H) mm
Weight	approx. 400 g
Certifications	EMC CE (EN 55032, EN 55024 Class B, EN 50121-4, EN 50121-3-2), FCC (FCC Part 15 Subpart B Class B), RCM (AS/NZS CISPR 32 Class B), VCCI (VCCI-CISPR 32 Class B) Safety UL (UL 62368-1), CB (IEC/EN 62368-1, IEC/EN 60950-22, IEC/EN 62471) Environment IK10, IP66/67, NEMA 4X Railway EN 50155: 2021 (OT1), EN 50121-3-2:2016, EN 60068-2-1:2007, EN 60068-2-2:2007, EN 61373:2010, EN 45545-2, IEC 60571 Ed 3.0, IEC 62236-3-2 Ed 3.0, EN 50121-4:2016 Vehicles ECE R118
Operating Temperature	Starting Temperature: -25°C ~ 55°C (-13°F ~ 131°F) Working Temperature: -25°C ~ 60°C (-13°F ~ 140°F) (IR off) -25°C ~ 55°C (-13°F ~ 131°F) (IR on) Maximum (intermittent): 70 °C (158 °F)
Humidity	98% RH (non-condensing)
Storage Temperature	-40°C ~ 70°C (14°F ~ 158°F)
Warranty	60 months

System Requirements

Operating System	Microsoft Windows 8/7 Mac 10.12 (Chrome only)
Web Browser	Chrome 58.0 or above Internet Explorer 11
Other Players	VLC: 1.1.11 or above

Included Accessories

Packing Contents	Quick installation guide, alignment sticker, screw driver, desiccant bag
------------------	--